

**GBC** AUSTRALIA

# Panda 1600

**GBC Panda 1600**  
**The choice for value**  
**in Wide - Format**  
**Cold Lamination**



# Panda 1600

## Cold pressure sensitive laminator - designed for heat-sensitive material

The Panda 1600 is designed to protect and enhance the wide variety of inkjet prints that are sensitive to heat and cannot be finished using thermal-activated films.

The Panda 1600 can laminate and mount prints up to 60" (1580mm) wide using pressure-sensitive film and foam boards.

Use GBC's new Arctic & Krystal PSA Films and see how "cool" your prints can be!

## Cool Arctic & Krystal PSA Films

### PSA Overlamines

- \* Pro-Gloss UV
- \* Pro-Satin UV
- \* Pro-Matte UV
- \* Sand Texture
- \* Grafitti
- \* Satin Texture

### PSA Mounting Films

- \* Pro-Mount
- \* Floor Mount
- \* Krystal Mount (Solvent)
- \* White Mount

### Backing Film

- \* Up to 1580mm

## Cool Features

- \* Scrap take-up reel conveniently winds release liner
- \* Roller gap adjusts up to 20mm for mounting
- \* Adjustable speed for operator comfort
- \* Foot pedal allows hands-free operation
- \* Stand rolls easily for maximum mobility
- \* Reversible motor clears feed jams



### Applications

- \* Photo Murals
- \* Window Decaling
- \* Graphic Mounting
- \* Trade Show Displays
- \* POP Display
- \* Floor Graphics

## Specifications

	Panda 1600
Max Laminating Width:	1580mm
Max Mounting Thickness:	25mm
Highest Linear Speed:	2m/min
Lowest Linear Speed:	0.7/min
Power Requirements:	220 V 50Hz (100V 60Hz)
Nominal Output Power:	70W
Contour Dimension:	2010 x 680 x 471mm
Net Weight:	215kg
Weight In Transport:	265kg
Core Size:	76mm Core

\*Specifications are subject to change without notification