

enhance your business with gbc dna

Delta

automatic laminator



The finishing touch for the on-demand market.

GBC LAMINATION
gene therapy for your business

Delta



The delta is a synonym for flexibility.

Where volumes are becoming smaller and production turn-around needs to be more efficient, the Delta concept is based on offering you the ability to change stock, size and film quickly.

This one-sided, cost competitive laminator is a compact, fully integrated machine with a built-in feeder and separator. It is suitable for shorter runs and offers high professional and quality performances.

The Delta's compact design, speed of 20m/min and ease of operation makes it the ideal machine to start inhouse lamination and add flexibility to existing lamination facilities.

The Delta will surely help you to distinguish yourself and to offer your customers the best quality and fast service they rely on.

APPLICATIONS:

**BOOK COVERS, MAGAZINE COVERS,
PACKAGING, BROCHURES, POCKET FOLDERS**



www.gbcaustralia.com.au

ph 1800 422 349 fax 1800 819 985

Sydney Melbourne Brisbane Canberra Adelaide Perth Hobart Darwin

specifications

<i>sheet size</i>	
<i>minimum</i>	200 mm x 200 mm
<i>maximum</i>	520 mm x 740 mm
<i>max speed</i>	30m/minute (equals 6,000 A3 sheets / hour)
<i>paper weight</i>	130 gsm - 350 gsm
<i>max load capacity</i>	652 mm
<i>max film length</i>	3000 m
<i>film material</i>	GBC OPP 9325 GBC OPP 8300 GBC PET 8200 GBC HighTac Layflat GBC Layflat 8500
<i>dimensions</i>	
<i>length</i>	1800 mm
<i>width</i>	1600 mm
<i>height</i>	1450 mm
<i>power</i>	380V AC 50Hz, 3 Phase, 17 Amp +N +E
<i>weight</i>	850 kg
<i>air consumption</i>	120 litres per minute @ 7 bar

features

The machine will be installed and your operator trained by our technical staff who offer the technical after-sales service.

A dual zone, electrical heated chrome laminating roller means a variety of different sizes can run on the machine and whilst maintaining a stable temperature

Knicking knife and a variable snap roller combination assures constant and clean film separation

Easily adjustable decurl bar ensures decurling of sheets for flat finished products

User friendly control panels. Easily controlled by a single operator

Film rolls can be easily loaded using a simple locking mechanism